



GERMAN TECHNOLOGY - GERMAN INNOVATION

Service Car Technology Vertriebs GmbH Hasenkamp. 4 22880 Wedel/Hamburg Germany

QUALITY CERTIFICATE

Senfineco SynthPro 5W-30 C4 RN0720

Properties

SynthPro 5W-30 C4 RN0720 is a HC-synthetic high-Performance low viscosity engine oil with low sulphur, ash and phosphorus content (low SAP). Base oils of the latest HC-synthesis technology and a corresponding high-performance additive with lowered sulphate ash guarantee best wear protection and highest engine cleanliness. Excellent cold start behavior ensures optimum lubrication reliability in the cold running phase. Extreme loads and high temperatures are safely mastered.

SynthPro 5W-30 C4 RN0720 can be used under all operating conditions and contributes to environmental protection by reducing pollutant emissions.

Application notes

SynthPro 5W-30 C4 RN0720 was developed especially for Renault diesel engines with particle filters (DPF's).

Except 2.2dCi / G9T engine!

SynthPro 5W-30 C4 RN0720 optimizes the service life of exhaust gas purification systems and maintain their functionality.

Service description

Specifications:

- ACEA C4

Recommendations*:

- Renault RN0720
- MB 226.51

TYPICAL PARAMETERS	METHODS	UNITS	SynthPro 5W30 C4
Density at 15°C	DIN 51 757	kg/m ³	852
Viscosity at 40°C	DIN 51 562	mm ² /s	70
Viscosity at 100°C	DIN 51 562	mm ² /s	12
Viscosity at -30°C	DIN 51 377	mPa.s	5750
Viscosity Index (VI)	DIN ISO 2909	-	162
Pour point	DIN ISO 3016	°C	-36
Flash point COC	DIN ISO 2592	°C	230
TBN	DIN ISO 3771	mg KOH/g	7.3

* meets the requirements of the OEM manufacturer
The above values may vary within commercially accepted tolerances

Note:
No heavy metal was found in concentrations greater than 500 ppm. For this purpose, "metal" – molybdenum, manganese, calcium, zinc or magnesium.