



QUALITY CERTIFICATE

Senfineco GearUltra MVS WS

Properties

GearUltra MVS WS is a high-performance automatic transmission fluid based on HC-synthetic technology, developed to meet the demands of modern automatic transmissions. Its very high viscosity index and excellent viscosity – temperature behaviour ensure reliable performance over a wide operating range, including excellent low-temperature flow due to its low pour point. The advanced formulation provides high load-carrying capacity and outstanding wear reduction while preventing foam formation. High thermal and oxidation stability, combined with stable friction coefficient characteristics and neutrality towards common sealing materials, ensure long service life and consistent transmission performance.

Application notes

GearUltra MVS WS is suitable for use in automatic automotive transmissions and torque converters. It can also be applied in hydrostatic transmissions, power steering systems and selected hydraulic systems.

Observe manufacturer's instructions!

Service description

Recommendations*:

- Aisin Warner JWS 3309
- Allison C-4, TES-295, TES-389
- BMW/Mini P/N 81 229 400 272/275
- BMW/Mini P/N 81 229 407 858/859
- BMW/Mini P/N 83 220 024 249/359
- BMW/Mini P/N 83 22 0 026 922 (BMW 7045 E) / 83 22 9 407 765 (BMW LA2634)
- BMW/Mini P/N 83 22 0 402 413
- BMW/Mini P/N 83 22 0 403 248/249
- BMW/Mini P/N 83 22 7 542 290
- Chrysler/Dodge/Jeep AS68RC ATF
- Chrysler/Dodge/Jeep ATF+2/ ATF+3 / ATF+4 / SP-III
- Daimler/Mercedes MB 236.3 / 236.5 / 236.6/ 236.7
- Ford WSS-M2C919-E (Mercon V)
- Ford/Lincoln/Mercury P/N XT-2-QDX [M] / XT-2-QSM [Syn] / XT-5-QM or-DM [V]/ XT-8-QAW [Premium] / XT-9-QMM5 [FNR5]
- Ford/Lincoln/Mercury WSS-M2C922-A1
- GM Dexron II / II-D / II-E / III-G / III-H
- GM/GMC/Opel/Saturn P/N 19 40 700/767
- GM/GMC/Opel/Saturn P/N 21005966 (transaxle)/22717466
- GM/GMC/Opel/Saturn P/N
- GM/GMC/Opel/Saturn T-IV, Type A Suffix A
- Honda ATF-Z1
- Hyundai SP-II/ SP-III
- Jaguar JLM 20238 / 20292 / 21044 / K17
- Jaguar WSS-M2C922-A1
- JASO 1-A
- KIA SP-II/ SP-III
- Land Rover Texaco ETL-7045E
- MAN 339 A
- MB 236.8 / 236.9 / 236.10 / 236.91
- Mercon V
- Mitsubishi Diamond SP-II / SP-III
- Mobil ATF 3309
- Nissan Matic D/J/K/S
- Porsche P/N 000 043 204 41 / 000 043 205 09 / 999 917 547 00 (A2)
- PSA Peugeot Citroen P/N Z 000169756
- Renault Matic D2
- Renk Genuine Oil
- Saab 3309 - T-IV
- Shell 3403-M115, LA2634
- Texaco ETL 7045E / 8072B, N402
- Toyota T-III / T-IV
- Voith H55.6335.XX
- Voith Svc Bltn # 013 / 118
- Volvo P/N 1161521 / 1161540 / 1161640 / 1273,41



QUALITY CERTIFICATE

Senfineco GearUltra MVS WS

Service description

Recommendations*:

- VW/Audi G 052 025 A2 / G 052 055
- VW/Audi G 052 162 (A1, A2)
- VW/Audi G 052 990 (A2), G 055 025 (A2)
- VW/Audi US 000 162
- ZF TE-ML 11A/ 11B

TYPICAL PARAMETERS	METHODS	UNITS	GearUltra MVS WS
Density at 15°C	DIN 51 757	kg/m ³	850
Viscosity at 40°C	DIN 51 562	mm ² /s	38.2
Viscosity at 100°C	DIN 51 562	mm ² /s	7.0
Viscosity Index (VI)	DIN ISO 2909	-	150
Pour point	DIN ISO 3016	°C	-45
Flash point COC	DIN ISO 2592	°C	228
Colour	-	-	red

* meets the requirements of the OEM manufacturer
The above values may vary within commercially accepted tolerances

December 2024