



GERMAN TECHNOLOGY - GERMAN INNOVATION

Service Car Technology Vertriebs GmbH Hasenkamp. 4 22880 Wedel/Hamburg Germany

QUALITY CERTIFICATE

Senfineco GearUltra AG55 ATF

Properties

GearUltra ATF AG55 is a high-performance automatic transmission fluid developed for modern 6-speed automatic transmissions. Its advanced formulation ensures excellent load-carrying capacity and outstanding wear reduction, even under demanding operating conditions. Superior friction stability guarantees smooth and precise gear changes, including sporty shifting behaviour. **GearUltra ATF AG55** offers excellent low-temperature shifting performance, reliable protection against foam formation, and minimal evaporation losses. High oxidation and thermal stability, combined with neutrality towards common sealing materials, ensure long service life and consistent transmission performance.

Application notes

GearUltra AG55 is especially designed for modern ZF 6-speed automatic transmissions used in high-performance passenger vehicles. Due to its specific formulation, it can also be used in selected older ZF 5-speed automatic transmissions (ZF 5HP). **GearUltra AG55** is **not** suitable for use in double-clutch (DCT/DSG) or continuously variable (CVT) transmissions. **Observe manufacturer's instructions!**

Service description

Recommendations*:

- BMW ATF M 1375.4 (8322 0142516)
- Bentley Oil PY112995PA
- FORD MERCON SP/LV
- Hyundai SP-IV
- Jaguar Fluid 8432
- Land Rover TYK 500050
- Maserati Oil 231603
- Nissan Matic S
- Toyota Type WS
- VW / Audi G 055 005 A1/A2/A6
- ZF Lifeguardfluid6 (S671 090 255)

TYPICAL PARAMETERS	METHODS	UNITS	GearUltra Ag55
Thickness at 15°C	DIN 51 757	kg/m ³	853
Viscosity at 40°C	DIN ISO 3104	mm ² /s	31
Viscosity at 100°C	DIN ISO 3104	mm ² /s	6.1
Viscosity Index (VI)	DIN ISO 2909	-	154
Pour point	DIN ISO 3016	°C	-42
Flash point COC	DIN ISO 2592	°C	>170
Colour	-	-	yellow-brown

* meets the requirements of the OEM manufacturer
The above values may vary within commercially accepted tolerances